



# MASKING TAPE 80°C PRO

## Technical Data Sheet

### General Description

High-grade automotive masking tape recommended for demanding automotive repair workshops and high degree oven use. Saturated semi crepe paper masking tape coated with specially developed cross-linked solvent based natural rubber adhesive. Guaranteed for one hour, 80°C oven use. Also suitable for all general masking applications.

### Product Application

- Guaranteed spray painting automotive oven use in 80°C for 60 minutes
- General masking
- Domestic DIY and Industrial general painting
- Holding
- Sealing
- Fixing
- Light duty packaging

### Product Properties

- 80°C oven use for 60 minutes
- Suitable for both metallic and plastic automotive surfaces
- Absolute residue free removal
- Various surface options to cover special requirements.
- Excellent tape to tape adhesion
- Solvent and thinner resistant
- High initial tack
- Easy tear
- Excellent conformability
- Suitable for water and solvent based paints
- Easy curving
- Easy application on uneven surfaces

### Nominal Values

#### Backing

Impregnated Crepe Paper

#### Adhesive

Solvent-based, Natural Rubber

#### Tensile Strength MD

85 ± 20 (N/25mm) TM 5004 by Afera

#### Elongation at Break MD

9 ± 2 (%) TM 5004 by Afera

#### Adhesion to Steel

5 ± 1 (N/25mm) TM 5001 by Afera

#### Rolling Ball Tack

Under 2 (cm) PSTC-6 (PSTC)

#### Paper thickness

95 ± 15 (mic)

#### Application Range

80°C for 60 minutes

#### Paper Colors

White ○

#### Adhesive Color

Transparent ∅

For professional use only. The information displayed on this sheet has been carefully selected through a series of laboratory investigations. It is based on our best knowledge at the time of issue. The data is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check for newer updates or further information if needed for his intended purpose. The intellectual property of this product, trademarks and copyrights is protected. All rights reserved. The relevant Material Safety Data Sheet and warnings displayed on the label must be read carefully. We may modify and / or discontinue operation of all or portions of this information at any time in our sole discretion, without any notice and assume no responsibility to update the information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

Issue 1/2014, November 2014